HCNA Coax MDU Ethernet Endpoint

January 2010

Coax MDU Endpoint Bridge With In-Building Coax Last Meters Distribution Providing a Managed 224Mbps / 192Mbps High Speed Service

Last Meters Distribution of FTTB ...

No additional network wiring ...

The Most Powerful and Cost-Effective HCNA Solution with Remote Management.

Introduction

THE HCNA COAX MDU ETHERNET ENDPOINT, CES-630 / CES-631, IS THE BROADBAND ACCESS DEVICES OVER THE EXISTING COAXIAL CABLE.

NO ADDITIONAL NETWORK WIRING IS NECESSARY. CABLE OPERATORS MAY JUST USE THE EXISTING COAX WIRING IN THE MDU BUILDING, THEN BE READY TO PROVIDE THE BROADBAND TRIPLE-PLAY SERVICES TO SUBSCRIBERS.

LOW INITIAL DEPLOYMENT COST. DUE TO HIGH INITIAL COST OF CMTS AND DSL BASED SOLUTION, IT REQUESTS A HIGH SUBSCRIBER NUMBER TO DEPLOY THE SERVICE. THE LOW INITIAL COST CAN EXPAND THE SERVICE TO SMALL SCALE BUILDING WITH HIGHER SPEED THAN CMTS.

WITH CEM-638/CEM-639 MANAGEMENT, IT CAN MANAGE THE DEVICES REMOTELY TO MINIMIZE THE INSTALLATION AND SUPPORT COST.

THE UNIQUE ENDPOINT SERVICE CONTROL SUPPORTS SERVICE PROVIDERS WITH DIFFERENT SERVICE LEVELS AND SERVICE SCHEMES.



Model: CES -630 / CES-631

FEATURES

- Design for Operators Providing High Speed Service over Coax Network
- HCNA up to 224 / 192 Mbps PHY Rate as Distribution Backbone over Coax
- Two 10/100M Fast Ethernet Ports
- Up to 65dB Attenuation on Coax Network
- Filter Built-in to Eliminate Noise from TV
- QoS Priority and Mapping Support
- Queuing Schemes for Variant QoS Demand
- > TagVLAN Configuration
- Service and Bandwidth Control
- > IGMP Snooping Control